


Powerful and Flexible Transmitter

Touch the Future




Intelligent diagnostics utility

- Unique iMonitor function
- Intelligent diagnostics with traffic light indication of sensor status
- Predictive maintenance using ISM technology



Intuitive touchscreen control

- State-of-the-art user interface
- Large color display
- Simple and self-explanatory operation



Information at a glance

- Simultaneous display of one to four measurement points
- Configurable display
- Setup of "Favorites" menu to directly access frequently used menus



Flexible configuration

- Multi-parameter transmitter
- Mixed-mode (M800 1-channel) input to use analog or ISM sensors
- Multi-channel device reduces the cost per measurement



ISM™ US LISTED

M800 Process Transmitter

Complete Control at Your Fingertips

The M800 multi-parameter transmitter provides simultaneous monitoring of one, two or four in-line sensors for measurement of pH/ORP, optical DO, amperometric oxygen (DO as well as O₂ gas), conductivity, CO₂ and turbidity in process applications.

The Profinet and Ethernet/IP interfaces provide easy integration of sensor diagnostic tools into process control systems, reduce commissioning time and engineering support, and save integration efforts and costs. Digital communication within the loop, plus real-time measurements and sensor diagnostics, provide greater process reliability and lower maintenance costs.

Intelligent Sensor Management (ISM™) features in the M800 include Plug and Measure for fast sensor installation and startup, predictive maintenance information and dynamic sensor lifetime status. The M800 line is also available in a hygienic version with a stainless steel housing.

► www.mt.com/M800

METTLER TOLEDO

Technical data of the M800 Process 1-channel, 2-channel and 4-channel transmitter series

Designation	M800 1-channel	M800 2-channel	M800 4-channel	M800 Profinet and Ethernet/IP 1-/2-channel
Measurement parameters				
pH/ORP	•	•	•	•
Dissolved and gaseous oxygen	•	•	•	•
Dissolved CO ₂	•	•	•	•
Conductivity	•	•	•	•
Turbidity	•	—	—	•*
Approval	Stainless steel Polycarbonate	CE/UL CE	CE/UL FM Cl.1 Div2, UL	CE/UL ** CE/UL
Current outputs (galvanically isolated)	4 × 0/4 to 20 mA	8 × 0/4 to 20 mA	8 × 0/4 to 20 mA	1 × 0/4 to 20 mA (for M800 Ethernet/IP 1-/2-ch) None (for M800 Profinet 1-/2-ch)
Digital inputs	4	5	6	5
Sensor type	Mixed-mode (analog, ISM)	ISM	ISM	ISM
ISM features	Plug and Measure, advanced diagnostic tools (DLI, ACT, TTM), iMonitor			
Power	AC (100–240 V) or DC (20–30 V)			
Enclosure	Stainless steel Polycarbonate	½ DIN, IP 66 ½ DIN, IP 66	½ DIN, IP 66 ½ DIN, IP 66	½ DIN, IP 66 ** ½ DIN, IP 66
Relays	8	8	8	2
Analog input (galvanically isolated)	1 × 4 to 20 mA (for pressure compensation)			
Multi-level password protection	Yes			
User interface	Color touchscreen, 5.7" TFT, 320 × 240 pixels, 256 colors			
Service interface	USB port			

* Only one turbidity or optical DO sensor can be connected to the transmitter at the same time.

** Stainless steel version is only available for EIP 2-channel

Ordering information

Designation	Order No.
M800 Process 1-channel	30 026 633
M800 Process 2-channel	52 121 813
M800 Process 4-channel	52 121 853
M800 Process 1-channel SST	30 246 551
M800 Process 2-channel SST	30 246 552
M800 Process 4-channel SST	30 246 553
M800 Process 1-channel Profinet	30 530 021
M800 Process 2-channel Profinet	30 530 022
M800 Process 1-channel EtherNet/IP	30 530 023
M800 Process 2-channel EtherNet/IP	30 530 024
M800 Process 2-channel EtherNet/IP SST	30 943 682

► www.mt.com/M800

ISM is a trademark of the METTLER TOLEDO Group.
All other trademarks are the property of their respective owners.



METTLER TOLEDO Group
Process Analytics
Local contact: www.mt.com/contacts

Subject to technical changes
05/2024 © METTLER TOLEDO
All rights reserved. PA2046en G
MarCom Urdorf, CH

www.mt.com/pro

For more information