



SMALLEST & LIGHTEST 5 GAS MONITOR

Gas Detection For Life

GX-3R Pro Model



5 World's Smallest and Lightest Gas Monitor

Features

- **Smallest & lightest 5 gas monitor**
— 2.9" W x 2.6" H x 1.06" D , 4.58 ounces
- **Simultaneous detection of 5 gases**
— Confined Space Gases: LEL, O₂, H₂S, CO
— Toxic/IR Gases: HCN, NH₃, NO₂, PH₃, SO₂, and CO₂
— H₂ Compensated CO sensor available
- **Simple 2-button operation**
- **Bluetooth communication with iOS & Android App**
- **Non-Compliance Indicator**
- **3 user adjustable alarm levels**
- **Panic Alarm**
- **Man Down Alarm**
- **Impact resistant body**
- **Large full dot, auto-backlit display with auto-rotation**
- **Stealth mode for law enforcement**
- **Field replaceable sensors & filters**
- **Water and dust resistant design, IP66/68**
- **3 Year Warranty***

Applications

- **Personal monitoring**
- **Confined spaces**
- **Refineries / petrochemical**
- **Utilities**
- **Oil and Gas**
- **Water / wastewater**
- **Fire services**
- **Construction**

The GX-3R Pro is the world's smallest 5-gas monitor weighing only 4.58 ounces and fits in the palm of your hand (2.9" W x 2.6" H x 1.06" D). It simultaneously monitors and displays 5 different gases. In addition to monitoring standard confined space gases, LEL, O₂, CO, & H₂S, the GX-3R Pro has a 5th channel where you can add infrared or toxic gas sensors. Two of the four sensor slots have interchangeable sensors providing flexible configurations, which can easily be changed in the field.

The GX-3R Pro comes equipped with Bluetooth wireless communication, man-down alarm, the choice of alkaline or rechargeable power supply, and a 3 year warranty. The Lithium-ion battery pack will operate for 25 hours and will fully charge in 3 hours.

The GX-3R Pro utilizes Bluetooth communication to display direct gas readings from the instrument to a phone app, which is available free on either iOS or Android phones. Automatic notifications can be programmed to send text or email messages if there is an alarm event from the GX-3R Pro.

Safety supervisors will appreciate the non-compliance indicator. The instrument flashes it's 3 LED lights every 30 seconds in the following conditions; if the instrument has not been bump tested, or if calibration is due, or if there was a gas alarm event. The 3 LED lights will continue to flash once every 30 seconds until the non-compliance condition has been resolved. The 30 second interval is adjustable.

* 3 year warranty on material and workmanship including sensors (1 year for Ammonia sensor)



RKI Instruments, Inc. • 33248 Central Ave. Union City, CA 94587 • Phone (510) 441-5656 • (800) 754-5165 • Fax (510) 441-5650

World Leader In Gas Detection & Sensor Technology
www.rkiinstruments.com

GX-3R Pro Model

Detectable Gases					Common Specifications								
Gas		Measuring Range (Increments)	Accuracy Statement	Preset Alarms		Sampling Method	Diffusion sampling standard (hand aspirator or clip-on motorized pump optional)						
Sensor Slot 1: Carbon Monoxide (CO) & Hydrogen Sulfide (H2S)													
H2S / CO	Dual EC	0 ~ 2000 ppm (1 ppm)	± 5% of reading or ± 5 ppm CO	A1: 25 ppm A2: 50 ppm A3:1200 ppm	STEL: 200 ppm TWA: 25 ppm	Alarm Types	Gas Alarm		Trouble Alarm				
		0 ~ 200.0 ppm (0.1 ppm)	± 5% of reading or ± 2 ppm H2S	A1: 5 ppm A2: 30 ppm A3: 100 ppm	STEL: 5.0 ppm TWA: 1.0 ppm		• 2 increasing alarms • STEL • TWA • Overscale alarm • O2 decreasing/ increasing	• Sensor disconnection • Low battery • Circuit error • Calibration range error • Cal or bump due alarm					
H2S Only	EC	0 ~ 200.0 ppm (0.1 ppm)	± 5% of reading or ± 2 ppm H2S	A1: 5 ppm A2: 30 ppm A3: 100 ppm	STEL: 5.0 ppm TWA: 1.0 ppm		• Man Down Alarm • Panic Alarm						
CO H2 Compensated	EC	0 ~ 2,000 ppm	± 5% of reading or ± 2 ppm CO	A1: 25 ppm A2: 50 ppm A3: 1200 ppm	STEL: 200 ppm TWA: 25 ppm		Display of Alarm	Gas Alarm		Trouble Alarm			
Sensor Slot 2: Combustibles (Methane as standard)									• Flashing LED's • Continuous buzzer (100 db @ 30cm) • Flashing gas value • Vibration	• Flashing LED's • Intermittent buzzer (95 db @ 30cm) • Display of error message			
CH4 / HC	Catalytic	0 ~ LEL (1% LEL)	± 5% of reading or ± 2 % LEL	1st: 10% LEL 3rd: 50% LEL	2nd: 25% LEL Over:100% LEL	Operating Temp. & Humidity	-20°C ~ +50°C [-4°F ~ +122° F] 10 to 90% RH, non-condensing (continuous environment)						
Sensor Slot 3: Oxygen (O2)									-40°C ~ +60°C [-40°F ~ +140°F] 0 to 95% RH, non-condensing (temporary environment)				
O2	EC	0 ~ 40.0% Vol. (0.10%)	± 0.5% O2	Low 1: 19.5% Low 2: 18.0%	High: 23.5% Over: 40.0%	Response Time	Within 30 seconds (T90)						
Sensor Slot 4: Toxics & CO2													
HCN	EC	0 ~ 30.0 ppm (0.1 ppm)	± 10% of reading or ± 5 % of full scale	A1: 5.0 ppm A2: 10.00 ppm A3: 30.00 ppm	STEL: 10 ppm TWA: 4.7 ppm	Power Source	Config	Li-ion	Alkaline				
NH3		0 ~ 400.0 ppm (0.5 ppm)		A1: 25.0 ppm A2: 35.0 ppm A3: 300.0 ppm	STEL: 1.0 ppm TWA: 0.30 ppm		4-gas + EC	25 hours	16 hours				
NO2		0 ~ 20.00 ppm (0.05 ppm)		A1: 2.00 ppm A2: 4.00 ppm A3: 20.00 ppm	STEL: 25.0 ppm TWA: 35.0 ppm		with BLE	23 hours	14 hours				
PH3		0 ~ 20.00 ppm (0.01 ppm)		A1: 0.30 ppm A2: 0.60 ppm A3: 0.60 ppm	STEL: 1.0 ppm TWA: 0.30 ppm		4-gas + IR	16 hours	7 hours				
SO2		0 ~ 100.0 ppm (0.05 ppm)		A1: 2.00 ppm A2: 5.00 ppm A3: 100.00 ppm	STEL: 5.0 ppm TWA: 2.00 ppm		with BLE	15 hours	6 hours				
CO2 %	IR	0 ~ 10.0% Vol. (0.01%)	± 5% of reading or ± 2 ppm	A1: 0.50% Vol. A2: 3.00% Vol. A3: 4.00% Vol.	STEL: 3.00% Vol. TWA: 0.50% Vol.	Dimension & Weight	2.9" W x 2.6" H x 1.06" D (Approx. 73 W x 65 H x 26 D mm) 4.58oz (with rubber boot)						
CO2 ppm		0 ~ 10,000 ppm (20 ppm)		A1: 5,000 ppm A2: N/A	STEL: N/A TWA: N/A	Case Material	Dust and water resistant to IP-66/68 (2m,1h); Drop test height 23 ft						
Calibration Station SDM-3R					Clip-On Sampling Pump RP-3R					Bluetooth Communication		BLE: with iOS and Android phone app: <i>RK Link</i>	
										Datalogging		Logs user ID, station ID, Calibration & Bump Test history, Alarm Events & Alarm Trends	
										Standard Accessories		Alligator clip, protective rubber boot, charger, cali- bration adapter	
										Optional Accessories		• Padded carrying case • RP-3R Attachable sampling pump with 4" rubber nipple, 10' hose and probe (up to 100' hose available) • USB to IrDA downloading cable for datalogger • SDM-3R calibration station • Hand aspirator	
										Approvals		ATEX, CSA, IECEx, MED	
										Warranty		3 years material and workmanship including sensors (1 year for Ammonia sensor)	

*Specifications subject to change without notice



INSTRUMENTS
Gas Detection For Life

(800) 754-5165
www.rkiinstruments.com

Authorized Distributor: